


F-529-7NDC Finish(C)

F-529-7NDGS Finish(GS)



- Integrated Handle
- Spot Defense™
- Pforever Seal™

Specifications

Features

- 1.8 GPM Flow Rate
- Spot Defense™ Finish which Resists Spots and Fingerprints (GS Finish Only)
- 1, 2, 3, or 4-Hole Installation; Deck Plate or Single Hole Mounting Option
- 2 Function Pull-Down Sprayer
- AccuDock™ Sprayhead Docking
- 360° Rotating Spout
- Nylon Flex-Lines Supply Lines
- Forward Handle Design
- Pfaster Connect™
- Swivel Spout
- Soap Dispenser
- TiteSeal™ Technology
- Quick Install Tool
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:


- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)



Dimensions



Optional Included Deckplate



Soap Dispenser

