


- F-529-7ZNRB Finish(B)
- F-529-7ZNRBG Finish(BG)
- F-529-7ZNRBBG Finish(BBG)
- F-529-7ZNRRC Finish(C)
- F-529-7ZNRGS Finish(GS)



Specifications

Features

- 1.66 GPM Flow Rate
- 1, 2, 3 or 4-Hole Installation; Optional Deck Plate Included
- 3 Function Pull-Down Sprayer (Spray, Stream, and Pause)
- MagnePfit™ Sprayhead Docking
- 360° Rotating Swivel Spout
- Forward Handle Operation
- SoloTilt™ One-Handed Soap Dispenser
- Nylon Braided Flex Hose
- 3/8" Connections
- 36" Integrated Flexible PERT Supply Lines
- 16.5" Extended Pull-Down Hose Length
- Spot Defense™ Finish Resists Spots and Fingerprints (GS Finish Only)
- Quick Install Tool
- Pfast Connect™ Adapter Technology
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:


- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
 - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant - ANSI A117.1 (Lever Handle Only)




Dimensions



Optional Included Deckplate



Top Filling Soap Dispenser



36 Inch Supply Lines with 3/8 Female Compression Brass Connections

